


BK 45, BK 46
DN 15, 20, 25



BK 15, DN 40, 50

Features of the BK series

- Robust regulator for roughest operating conditions (unaffected by waterhammer and frost)
- Suitable for superheated steam applications
- Automatic air-venting (steam trap can be used for thermal air-venting in steam systems)
- Installation in any position (horizontal and vertical lines)
- Stage nozzle acts as non-return valve
- Stainless steel internals
- Repairable in-line
- Base bushing ensures positive metal-to-metal sealing between body and regulator.
- Up to Δp 250 bar g
- Optional extra: Integrated steam trap monitoring for BK 45 (temperature or steam loss)

Application

For open-loop controlled heating processes.

Draining of

- saturated steam lines
- superheated steam lines
- steam tracers

Can also be used for thermal air-venting

Air-venting

Steam trap for thermostatic air-venting with bimetallic regulator

The thermostatic steam traps with corrosion-resistant Duo S.S. (bimetallic) regulator of the BK series can also be used for air-venting.

Application

Thermostatic steam trap for automatic air-venting and discharge of non-condensable gases and steam/air mixtures from steam lines and heat exchangers. Special adjustment might be required.

Pressure/Temperature Ratings *)

Type	PN Class	Δ PMX [bar]	Material		Max. Pressure / Temp. Rating	
			EN	ASTM	PMA / TMA	PMA / TMA
BK 45 ¹⁾	PN 40	22	P250 GH ²⁾	A105 ²⁾	28.4 bar / 250 °C	23.1 bar / 400 °C
BK 15 DN 40 / 50	PN 40	22	P250 GH ²⁾	A105 ²⁾	28.4 bar / 250 °C	23.1 bar / 400 °C
BK 46 ⁵⁾	PN 40	32	1.5415	A182 F 1 ³⁾	30.2 bar / 300 °C	25.8 bar / 450 °C
BK 37	PN 63/100	45	1.5415	A182 F 1 ³⁾	100.0 bar / 350 °C	34.3 bar / 530 °C
BK 27N DN 40 / 50	PN 63	45	1.5415	A182 F 1 ³⁾	47.6 bar / 300 °C	25.8 bar / 500 °C
BK 28	PN 100	85	1.5415	A182 F 1 ³⁾	100.0 bar / 350 °C	34.3 bar / 530 °C
BK 29	PN 160	110	1.7335	A182 F 12	146.1 bar / 350 °C	44.5 bar / 540 °C
BK 212	PN 630	250	1.7383	A182 F 22 ²⁾	447.5 bar / 500 °C ⁴⁾	163.0 bar / 580 °C ⁴⁾
BK 212-F91	–	250	1.4903/F91	–	932.9 bar / 500 °C	348.4 bar / 600 °C
BK 37-ASME	Class 400/600	45	–	A182 F 12	67.0 bar / 450 °C	42.0 bar / 500 °C
BK 28-ASME	Class 600	85	–	A182 F 12	80.4 bar / 350 °C	50.6 bar / 500 °C
BK 29-ASME	Class 900	110	–	A182 F 12	120.7 bar / 350 °C	43.6 bar / 540 °C
BK 212-ASME	Class 2500	250	–	A182 F 22	231.7 bar / 500 °C	63.0 bar / 593 °C

¹⁾ Also available: BK 45 U (discharges condensate with approx. 30 K undercooling).

²⁾ Material complies with EN and ASTM requirements.

³⁾ Physical and chemical properties comply with EN grade.

ASTM nearest equivalent grade is stated for guidance only.

⁴⁾ With special nuts and bolts.

⁵⁾ BK 46 replaces BK 16.

^{*}) For more information see data sheet.

